

BKM KS Soffit plate

Mineral soffit panel made of calcium silicate, pre-primed on the room side technical data sheet

Article-No.: H-001-955

Product description

Product advantages

- Moisture regulating
- Mildew inhibiting
- Non-combustible
- Capillary active
- Room side pre-primed on the sanded panel side
- Environmentally compatible due to the use of natural raw materials

Specification

Material:	Calcium silicate, cellulose fibers
Fire behavior:	Class A1 according to EN 13501-1:2010
	(according to ETA-19/0559)
Water vapor diffusion resistance number: $\mu = 3$	
Thermal conductivity	: $\lambda D (23,50) = 0,059 W/(mK)$
	λ Rated value = 0,062 W/(mK)
	(according to ETA-19/0559)
Density range:	180 kg/m³ – 187 kg/m³
Compressive strength	: ≥ 1.000 kPa
Water absorption coe	fficient: 46 kg/m²√h
Water saturation:	920 kg/m³
pH-value:	ca. 10
Environmental Product Declaration: EPD-CSP-20180010-IBC1-DE	

Application areas

The BKM KS reveal panel compensates for thermal bridges in the area of window and door reveals indoors, thus preventing mold growth.

Product application

Application

The structure of the BKM KS reveal panel corresponds to the structure of the BKM KS climate panel PRO, therefore the same processing guidelines and specifications for substrate preparation and surface coating generally apply.

The BKM KS reveal panel is placed, for example, in the area of the window on the front side of the frame. To prevent cracks, it is recommended to insert a compression tape in the connection joint. Decoupling from other adjacent components such as floors and ceilings with a further compression tape should be provided.

In addition, corrosion-free corner protection rails (e.g. made of plastic or aluminum) should be used and fixed with BKM KS special adhesive. Arched and vaulted soffits can be adapted by using smaller segment strips and bevel cuts.

Hinweise

Packaging unit 250 x 500 x 15 mm / 20 pcs. is Package / H-001-955

Legal notice

The above information, in particular the suggestions for processing and use of our products, are based on our knowledge and experience under normal circumstances, provided that the products have been stored and applied correctly. Due to the different materials, substrates and divergent working conditions, a guarantee of a working result or a liability, regardless of the legal relationship, cannot be justified on the basis of these instructions or verbal advice, unless we are accused of intent or gross negligence in this respect. In this respect, the user must prove that all knowledge necessary for a proper and promising assessment by BKM was provided to BKM in writing, in time and in full. The user must check the suitability of the products for the intended application. We reserve the right to make changes to product specifications.

Proprietary rights of third parties must be respected.

The latest product data sheet applies and must be requested from us. The responsibility for the successful application of our products lies with the user, as the use is beyond our control. However, we ensure the quality of our products in accordance with our conditions of sale and delivery, without guaranteeing the success of their application. Our data sheets represent advice based on our best knowledge, but no obligation can be derived from them. Our written consent is required to guarantee properties and application possibilities that go beyond the information recorded in the data sheets. **Further information can be found at:**

www.bkm-mannesmann.de

Copyright BKM.MANNESMANN AG - Wideystraße 23 - 59174 Kamen - Germany - Phone: +49 (0) 2307 9676.301 - www.bkm-mannesmann.de All rights reserved. Reproduction only with our permission.

Copyright BKM.MANNESMANN AG - Wideystraße 23 - 59174 Kamen - Germany - Phone: +49 (0) 2307 9676.301 - www.bkm-mannesmann.de All rights reserved. Reproduction only with our permission.